









# Projektierungshilfe für GuideLed SL CG-S

mit asymmetrischer Optik für E = 1,0 lx (0,5 lx)



Fluchtwegausleuchtung  
mit asymmetrischer Optik

Messebene 0,02 m, Wartungsfaktor WF = 80 %, Batteriebetrieb

Montagehöhe in Meter	Montagearten	L1 	L2 	L3 	L4 
2,5	Deckenmontage	2,3 (3,4)	6,8 (8,3)	6,4 ( 7,1)	14,1 (15,6)
3,0	Fluchtwegmitte	2,3 (3,2)	6,4 (9,2)	7,3 ( 8,1)	16,1 (17,8)
3,5		2,3 (3,2)	6,5 (9,7)	8,1 ( 9,0)	17,9 (19,9)
4,0		2,3 (3,3)	6,5 (9,4)	8,8 ( 9,9)	19,7 (21,9)
4,5		2,3 (3,3)	6,6 (9,1)	9,5 (10,7)	21,4 (23,7)
5,0		2,2 (3,3)	6,6 (9,2)	10,0 (11,5)	23,0 (25,6)
5,5		2,1 (3,3)	6,6 (9,2)	10,4 (12,2)	24,4 (27,4)
6,0		2,0 (3,3)	6,5 (9,3)	10,7 (12,9)	25,8 (29,1)
6,5		1,9 (3,2)	6,4 (9,4)	7,9 (13,5)	27,0 (30,8)
7,0		1,8 (3,1)	6,2 (9,4)	7,6 (14,0)	26,0 (32,3)
7,5		1,7 (3,1)	6,1 (9,3)	7,3 (14,5)	25,9 (33,7)
8,0		1,6 (2,9)	5,8 (9,3)	7,0 (14,8)	26,2 (35,2)
8,5		1,4 (2,8)	5,7 (9,3)	6,7 (15,1)	26,4 (36,6)
9,0		1,2 (2,8)	5,5 (9,1)	6,1 (14,9)	26,1 (37,8)
9,5		1,0 (2,7)	5,3 (9,0)	4,7 (10,9)	21,9 (37,6)
10,0		0,6 (2,5)	5,0 (8,8)	2,5 (10,7)	21,4 (36,7)